

Porti® Door opening restrictor

Doors are securely stopped & held!

- / Protection for door and frame: Stop and hold function with adjustable end position
- / Barrier-free & hygienic: Safe door environment without tripping hazards thanks to floor door stops & easy cleaning of surfaces and floors
- / Design-oriented: Concealed installation and flexible color adaptation
- / Space-saving: Slim lever arm allows use even with minimal frame clearance
- / Easy installation: Suitable for timber and glass doors, also for retrofitting
- / Tested durability: In accordance with DIN EN 13126-5, Class 4



Versatile Applications

/ Perfect for hospitals, care facilities, medical practices, hotels, offices, daycare centers, schools, and public buildings.





Stops, Holds, Hygienic, Barrier-Free




Technical Data

- / Slim lever arm: only 2 mm
- / Upper frame clearance: 4 10 mm

FOR GLASS DOORS

- / max. door leaf weight: up to 50 kg
- / guide rail adheres to the glass door leaf
- / compatible with ESG & VSG glass types




FOR TIMBER DOORS

- / max. door leaf weight: up to 100 kg
- / suitable for flush or rebated door leaves
- / also compatible with reverse-opening doors




FOR TIMBER AND METAL FRAMES

- / Timber frame:
 timber door up to 100 kg:
 Pre-installed with mounting element
 timber door up to 30 kg: Retrofittable
- / Metal frame: Timber door up to 100 kg: Retrofittable



ADAPTIVE DAMPING WITH HOLDING FUNCTION

- / Damping system stops slamming doors and prevents damage
- / Opening angle adjustable up to 120°
- / Holding function in end position prevents accidental closing (e.g., due to drafts)







	Timber door						Glass doors	
Door Leaf Width	720 - 1.100 mm			610 - 719 mm			709 - 959 mm	
Frame Material	Metal/ Timber	Timber	Metal	Metal/ Timber	Timber	Metal	Timber	Metal
Max. Door Weight	30 kg	100 kg	100 kg	30 kg	100 kg	100 kg	50 kg	50 kg
Retrofittable	Yes	No	Yes	Yes	No	Yes	No	Yes
Art. No.	5312	5489	5371	5313	5465	5379	5487	5318

